









SECTION A-A

M10X1.5 6H PER ASME B1.13M MINOR DIA.: 8.38-8.68

NOTE:

- GRIP RANGE: 0.5 3.5
- HOLE SIZE: 13.0 +0.1/-0.0 AFTER ALL APPLIED FINISHES.
- 3. INSTALLED LENGTH: 14.5 REF.
- LUBRICATION: NONE 4.
- 5. INS

	ALLATION TOOL: MS	100 SPIN PUL	.L								
				UNLESS OTHERWISE SPECIFIED:							
				DIMENSIONS ARE IN MILLIMETERS TOLERANCES:		NAME	DATE				
					DRAWN	JLA	8/11/03				
				ANGULAR: MACH±1 BEND ±1 TWO PLACE DECIMAL ±.10 THREE PLACE DECIMAL ±.05	CHECKED			TITLE:			
					ENG APPR.	JLA	8/11/03	SMALL FLANGE KNURLED BOD			
	PROPRIETARY AND CONFIDENTIAL THIS DRAWING, AND THE INFORMATION CON- TAINED HERIN, ARE THE PROPERTY OF SHEREX AND ARE NOT TO BE USED IN ANY MANNER DETRIMENT TO THE INTEREST OF THE COMPANY. SHEREX RESERVES THE RIGHT TO REVISE PART/DRAWING WITHOUT NOTICE.			INTERPRET GEOMETRIC TOLERANCING PER: ASME Y14.5M-1994	MFG APPR.	AJP	8/11/03	2WALL	RODA		
					Q.A.						
					COMMENTS:						
				MATERIAL C1008/C1010	E-mail: info@sherex.com www.sherex.com Phone: 866-474-3739 Fax: 716-875-0358			-	. NO.		REV
		NEXT ASSY	USED ON	FINISH ZINC PLATE W/YELLOW TRIVALENT CHROMATE PER SFS-01-001, SC2				A CKM2-1015-3.5			С
		APPLICATION		DO NOT SCALE DRAWING				SCALE: 2:1	WEIGHT: .0069 kg	SHEET	Г 1 OF 1

3