





M8X1.25 6H PER ASME B1.13M MINOR DIA .: 6.65 - 6.91

NOTE:

- GRIP RANGE: 0.5 3.0
- 2. HOLE SIZE: 11.0 +0.1/-0.0 AFTER ALL APPLIED FINISHES.

SECTION A-A

- 3. INSTALLED LENGTH: 11.0 REF.
- 4.
- LUBRICATION: NONE INSTALLATION TOOL: SPIN PULL

			LINILECC OTHERWISE CRECIEIED.							
			ANGULAR: MACH±1 BEND±1 TWO PLACE DECIMAL ±.10 THREE PLACE DECIMAL ±.05 INTERPRET GEOMETRIC TOLERANCING PER: ASME Y14.5M-1994	-		5.75				
					NAME	DATE				
				DRAWN	TOO	8/28/06				
				CHECKED			TITLE:			
				ENG APPR.	TOO	8/28/06	SMALL FLANGE KNURLED BOD			000
PROPRIETARY AND CONFIDENTIAL THIS DRAWING, AND THE INFORMATION CONTAINED HERIN, ARE THE PROPERTY OF SHEREX AND ARE NOT TO BE USED IN ANY MANNER DETRIMENT TO THE INTEREST OF THE COMPANY. SHEREX RESERVES THE RIGHT TO REVISE PART/DRAWING WITHOUT NOTICE.				MFG APPR.	AJP	8/28/06				ODY
				Q.A.						
				COMMENTS:			†			
			MATERIAL C1008/C1010	E-mail: info	sherex.com			DWG. NO.		REV
	NEXT ASSY	USED ON	FINISH ZINC PLATE W/YELLOW TRIVALENT CHROMATE PER SFS-01-001, SC2	Phone: 866-474-3739 Fax: 716-875-0358		A	A CKM2-8125-3.0		С	
	APPLICATION		DO NOT SCALE DRAWING			SCALE: 2:1	WEIGHT: .0040 kg	SHEET	1 OF 1	

5

3

2